



公差/General tolerances(mm)	
0	>3
~	>6
~	>10
~	>18
~	>30
~	>50
~	>80
~	>120
~	>180
~	>250
~	>315
~	>400
~	>500
±0.12	±0.18
±0.22	±0.26
±0.31	±0.37
±0.57	±0.80
±1.05	±1.15
±1.60	±2.20
±2.50	

ITEM	PART NAME	MATERIAL	NOTES
1	Housing	PA66-GF	UL94V-0
2	Cover	PA66-GF	UL94V-0
3	Button	PA66-GF	UL94V-0
4	Spring	Stainless steel	/
5	Clamp	Copper alloy	Plated Sn
6	Screw	Steel	Zn Plated

MATERIAL:			
MAT NO.:			
STATUS:			
APPD:			
CHKD:			
DRFT:			
SIZE: A4			
TYPE: A4			
SCALE: 1/1			
SHEET			

MATERIAL:			
MAT NO.:			
STATUS:			
APPD:			
CHKD:			
DRFT:			
SIZE: A4			
TYPE: A4			
SCALE: 1/1			
SHEET			



15ESAKNHBM -3.5

UL 标准/UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)	300/10	50/10	300/10
EC 标准/EC Standard:			
过压类别/Overvoltage Category/污染等级/ Pollution Degree	III/3	III/2	II/2
额定电压/电压/Rated Voltage(V)/Current(A)	160/13.4	160/13.4	320/13.4
额定脉冲电压(RV)/Rate Impulse Voltage(KV)	2.5	2.5	2.5
额定电压/电压/Rated Voltage(V)/Current(A)	0.2~1.5	28~16	
额定电压/电压/Rated Voltage(V)/Current(A)	3.50/N=04~48P		
额定电压/电压/Rated Voltage(V)/Current(A)	10~11		
额定电压/电压/Rated Voltage(V)/Current(A)	-40~+105		
符合RoHS要求/Conform to RoHS	Yes		